

Specifications

Driving method	Digital control servo motor	
Cutting method	Media-moving method	
Loadable material width	50 to 700 mm (2 to 27-1/2 in.)	
Maximum cutting area	Width: 584 mm (22-15/16 in.) Length: 24998 mm (984-1/8 in.)	
Acceptable tool	Special blade for CAMM-1 series	
Maximum cutting speed	500 mm/s (all direction)	
Cutting speed	10 to 500 mm/s (all directions)	
Blade force	30 to 250 gf	
Mechanical resolution	0.0125 mm/step (0.000492 in./step)	
Software resolution	0.025 mm/step (0.000984 in./step)	
Distance accuracy *1	Error of less than ±0.2 % of distance traveled, or ±0.1 mm, whichever is greater	
Repetition accuracy *1+2	±0.1 mm or less	
Alignment accuracy for printing and cutting when loading printed material *1+3	±1 mm or less for movement distance of 210 mm or less in material-feed direction and movement distance of 170 mm or less in width direction (Excluding effects of printer and/or material)	
Interface	USB Interface (compliant with Universal Serial Bus Specification Revision 1.1), Serial (RS-232C)	
Replot memory	800 Kbyte	
Instruction system	CAMM-GL III	
Power supply	Dedicated AC adapter Input: AC 100 to 240 V ±10 % 50/60 Hz 1.7 A Output: DC 24 V, 2.8 A	
Power consumption	Approx. 30 W (including AC adapter)	
Acoustic noise level	During operation	70 dB (A) or less (according to ISO 7779)
	During standby	40 dB (A) or less (according to ISO 7779)
Dimensions	855 (W) x 315 (D) x 240 (H) mm (33-11/16 (W) x 12-3/8 (D) x 9-7/16 (H) in.)	
Weight	16 kg (35 lb.)	
Environment	Temperature: 5 to 40 °C (41 to 104 °F), humidity: 35 to 80 % (no condensation)	
Included items	AC adapter, power cord, blade, blade holder, separating knife, roller base, tweezers, test-use material, application tape, USB cable, CD-ROM, user's manual	

*1 According to material and cutting conditions as specified by Roland DG Corp. (using the PNS-24 stand, sold separately).

*2 Excluding material expansion and contraction. Provided that media length is under 3000 mm.

*3 Using Roland CutStudio, a laser or inkjet printer having a resolution of 720 dpi or better. Excluding glossy or laminated material. Excluding effects of printing distortion due to printer precision and effects of material expansion, contraction, or warping. Depending on the ink (black) employed by the printer used, correct sensing may not be possible.

Options

Environmentally Friendly POP Series Sheets (Non-Chlorine Olefin Sheets)

Product number	Size	Description
POP-M-BK	305 mm x 10 m (12'x 32')	Matte black, 1 roll
POP-M-WH		Matte white, 1 roll
POP-M-RD		Matte red, 1 roll
POP-M-G2		Matte green, 1 roll
POP-M-YE		Matte yellow, 1 roll
POP-M-BL		Matte blue, 1 roll
AP-305		Transfer tape, 1 roll

*If the surface becomes covered with dirt and dust, wipe with water or neutral detergent. Do not use organic solvents or alcohol which can damage the material.

*These sheets, except black, are more transparent than commercially available vinyl sheets. Before gluing onto other sheets or darker materials, be sure to check that you are satisfied with the finished look of the job.

Blades

Product number	Offset value	Applicable cutting material	Quantity per package
ZEC-U5022	0.25 mm	Signage vinyl in general	2 pcs.
ZEC-U5025	0.25 mm	Thick, reflective and fluorescent vinyl, as well as signage vinyl in general	5 pcs.
ZEC-U3017	0.175 mm	Signage vinyl in general For cutting small letters or intricate designs	5 pcs.

Blade Holders

Product number	Description	Specifications
XD-CH3	Blade holder with blade extension adjuster, made of resin	Standard blade holder for working with signage vinyl in general.
XD-CH2	Blade holder with blade extension adjuster, made of aluminium	Blade holder for signage vinyl in general as well as thicker material. It also performs very well when creating detailed cutting.

Roller Base

Product number	Type of support	Material	Specifications
RSB-20	Four-point support	Resin	It is useful when working with rolled vinyl. Accommodates rolls of 300 mm (11-13/16 in.) width or wide. Rolls shorter than 300 mm cannot be accommodated.

Optional Stand
PNS-24



ISO 14001 and ISO 9001:2000 Certified

Roland pursues both environmental protection and continuous quality improvement. Under the philosophy of preserving the environment and human health, Roland DG is actively working to abolish organic solvents in production, to reduce and recycle waste, to reduce power use, and to purchase recycled products. Roland DG constantly strives to provide the most highly reliable products available.



Roland reserves the right to make changes in specifications, materials or accessories without notice. Your actual output may vary. For optimum output quality, periodic maintenance to critical components may be required. Please contact your Roland dealer for details. No guarantee or warranty is implied other than expressly stated. Roland shall not be liable for any incidental or consequential damages, whether foreseeable or not, caused by defects in such products. All trademarks are the property of their respective owners.

Roland®

AUTHORIZED DEALER:

Printed in Japan. RDG90328 '05 MAY A-4 G-S

www.rolanddg.com

Roland®

Desktop Sign Maker

CAMM-1 SERVO
GX-24



Quality Signmaking On Your Desktop.

Signmaking Has Never Been Easier.

With the CAMM-1 GX-24 vinyl cutter, you can create stand-out signage for your business in minutes. The GX-24 includes a host of advanced features that make it both powerful and easy to use. Even novices can master its operation in no time.



One Device For A Wide Variety of Applications


Roland's CAMM-1 vinyl cutters have been recognized worldwide as the industry's most cost-effective and reliable tools for producing banners, vehicle graphics, store displays, point-of-purchase materials, informational signs, backlit displays, flock heat transfers and almost any other vinyl cutting application. Powered by a digitally controlled servo motor for speed, precision and reliability, Roland CAMM-1 technology is now better than ever.

All-in-One Simplicity

Simply connect the GX-24 to your computer through the USB interface and you are ready to begin. It comes complete with everything you need to get started, including a Windows® driver and new CutStudio™ drawing application software. A newly designed blue LCD panel is perfectly positioned for easy viewing and navigation.

Roland CutStudio Design Software Included

Roland CutStudio is the perfect companion for your GX-24. Draw and edit circles and curves. Position your text along lines. It functions as a plug-in software for Adobe® Illustrator® 9/10/CS and CorelDRAW® 10/11/12, allowing you to create original graphics using popular design packages. It also imports graphic data from popular file formats including jpg, bmp, and both ai and eps formats from Adobe Illustrator versions 7 and 8. CutStudio accepts scanned images from TWAIN 32 scanners as well. CutStudio is compatible with Windows 98 SE/Me/2000/XP.



Produce Labels and Decals with Your Printer

With CutStudio, you can take any image printed on a commercially available printer and contour cut it. Use this feature to quickly produce labels and decals without special equipment. CutStudio also accommodates larger jobs by dividing them into tiles.

More GX-24 Features

- Fine tune your operation by adjusting blade-force with slide control, even while cutting.
- Store up to eight settings of regularly used blade and media combinations for quick recall.
- Two sets of guide lines (front and back) ensure precise media alignment.
- Front panel knife guide allows easy sheet trimming and removal of media.
- Test-cut function allows you to verify the machine's down force before you begin your job.
- An easy-to-attach sheet roller base helps ensure proper media feeding.
- A convenient tray on the back of the GX-24 stores blades and blade holders.

Simple Steps to Create Labels and Decals with the GX-24 and a Color Printer

